


MIXED MODE BENDING FIXTURE (AL AND SS) WITH FIVE SETS OF HINGES



Specimen:	Width	1.5"
	Thickness	Up to 0.25"
	Length	Up to 9.0"
Fixture:	Construction	Stainless steel and aluminum
	Temperature	-20°F to 120°F (-29 to 49°C)
	Mounting	1/4"-28 threaded coupling top, platen bottom
	Capacity	1,000 lbs (4.4 kN)
	Weight	Approximately 16 lbs
	Dimensions	10" x 2.5" x 8"
	Standard	Manufactured in accordance with ASTM D6671

Model No. ASTM.D6671.10 - Interlaminar Fracture Toughness Fixture

Includes base, lever, roller and roller holder, (5 sets of 2) hinges, saddle, loading yoke and ball bearing.

Accommodates specimens up to 1.5" in width, thicknesses up to 1/4", and lengths up to 9". Fixture is manufactured of aluminum and stainless steel in accordance with ASTM D6671. Fixture measures approximately 10" x 2.5" x 8".

LVDT not supplied with fixture. Temp range: -120 to 250°F (-85 to 122°C)

MODEL NO. ASTM.D6671.10

MIXED, MODE-I, MODE-II, INTERLAMINAR,

ACCESSORIES

Upper and lower fixture attachment is supported on a platen or flat surface of the test machine. (Common adapter sizes include:)

Model No. PLAT.RF061.10 - 6" Diameter Round Fixed Compression Platen

Model No. PLAT.RA061.10 - 6" Diameter Round Articulating Compression Platen

Model No. PLAT.SF061.10 - 6" Square Fixed Compression Platen

Model No. PLAT.SA061.10 - 6" Square Articulating Compression Platen

Model No. M03S36 - 1.25" Male Clevis (Type D) to 1" -14 Threaded Stud

SPARE PARTS

Contact us for spare or replacement parts

REFERENCE DOCUMENT AND TEST METHOD SCOPE:

<http://www.astm.org/Standards/D6671.htm>

ASTM D6671 / D6671M - 13e1

Standard Test Method for Mixed Mode I-Mode II Interlaminar Fracture Toughness of Unidirectional Fiber Reinforced Polymer Matrix Composites

1.1 This test method describes the determination of interlaminar fracture toughness, G_c , of continuous fiber-reinforced composite materials at various Mode I to Mode II loading ratios using the Mixed-Mode Bending (MMB) Test.

1.2 This test method is limited to use with composites consisting of unidirectional carbon fiber tape laminates with brittle and tough single-phase polymer matrices. This test method is further limited to the determination of fracture toughness as it initiates from a delamination insert. This limited scope reflects the experience gained in round robin testing. This test method may prove useful for other types of toughness values and for other classes of composite materials; however, certain interferences have been noted (see Section 6). This test method has been successfully used to test the toughness of both glass fiber composites and adhesive joints.

1.3 The values stated in either SI units or inch-pound units are to be regarded separately as standard. The values stated in each system may not be exact equivalents; therefore, each system shall be used independently of the other. Combining values from the two systems may result in non-conformance with the standard.

1.4 This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.

Extracted, with permission, from ASTM D6671 Standard Test Method for Mixed Mode I-Mode II Interlaminar Fracture Toughness of Unidirectional Fiber Reinforced Polymer Matrix Composites, copyright ASTM International, 100 Barr Harbor Drive, West Conshohocken, PA 19428. A copy of the complete standard may be purchased from ASTM International, www.astm.org.