



**Standards:**

ASTM D829 - 95

ISO 3781

ISO 12625

TAPPI 456

**Material Type:**

**Type of Testing:**

# NEW FINCH WET STRENGTH DEVICE

**Model No.**

ASTM.D0829.10

TAPI.00456.10

**Specimen Size or Difference Between Fixtures**

1" wide by 10" long

1" wide by 10" long

**Construction**

Stainless steel

Stainless steel

**Temperature**

-240 to 600°F (-152 to 318°C)

-240 to 600°F (-152 to 318°C)

Fixture:

Mounting

Grips (not included)

Capacity

Weight

Dimensions

Standard

Manufactured in compliance with ASTM D829 and TAPPI 456

## **QUOTE**

Model No. ASTM.D0829.10 - The New Style for the Finch Wet Strength Test Fixture

The fixture consists of reversed stirrup like design that the specimen wraps around and a vertical moving bath. Grips are needed for mounting the fixture to your testing frame (grips are sold separately). The fixture can handle a temperature range of -240 to 600°F (-152 to 318°C) and is made from stainless steel. Manufactured in compliance with ASTM D829 and TAPPI 456.

## **ACCESSORIES**

Model No. GRIP.10100.20 - 200 lbs Screw Action Grip Set with 1" x 1" Faces

Includes 1" x 1" flat square grip faces - The grips include two aluminum housings with a black anodized finish, and two screw-cam assemblies, which move the grip faces in and out. Supplied with (2) 1/2"-20 threaded stud and locking nut. Constructed of aluminum and steel with a protective finish. Manufactured in compliance with ASTM D624, D751, D882, D1000 and D1593.

## **SPARE PARTS**

Please contact us for spare or replacement parts

## **COMMON SIZE ADAPTERS**

### **Upper and Lower Mounting: 1/2"-20 Stud and Locking Nut**

Model No. M01C21 - 1/2" Male Clevis to 1/2"-20 Coupling

Model No. M02C21 - 5/8" Male Clevis to 1/2"-20 Coupling

Model No. M03C21 - 1.25" Male Clevis to 1/2"-20 Coupling

Model No. M12C21 - 12mm Male Clevis to 1/2"-20 Coupling

Model No. S36C21 - 1"-14 Stud to 1/2"-20 Coupling